

## HOUSEHOLD DEHUMIDIFIER

## Dry Digit 20 LCD

### Provided with:

- Electronic Control
- Display LCD
- Elegant and refined design

### Peculiarities:

- Round smooth not finned pipe Evaporator
- Two speed fan
- Low Power Consumption
- Color: Ivory white

### Used mainly in:

- Houses, Kitchen
- Laundries
- Shops
- Libraries



### TECHNICAL DATA:

Rated Maximum Power absorbed (at 20°C, 60% R.H.)	320 W
Rated Maximum Power absorbed (at 35°C, 95% R.H.)	440 W
Max. Current Absorbed (at 35°C, 95% R.H.)	2.3 A
Air Flow	250 mc/h
Sound Pressure Level (at 3 mts in free field)	38 db(A)
Refrigerant	R410a
Defrosting Control System	electronic
Capacity of Condensed Water Tank	6 Lt
Functioning Temperature Range	6-35 °C
Functioning Relative Humidity Range	40 - 99 %
Rated Condensation Capacity (at 30°C - 80 %)	20 l/ 24h
Rated Condensation Capacity (at 32°C-90 %)	22 l/ 24h
Weight with empty tank	12,7 kg
Dimensions LxDxH mm	362x270x582
Dimensions with Packaging Carton Boxes LxDxH mm	390x300x625
Number of Units in 40' (20') container	circa 980 (450)
Voltage Available:	230/1/50

### CONDENSED HUMIDITY AT DIFFERENT TEMPERATURES AND R.H. CONDITIONS

Room conditions	Condensed Water
10°C - 60%	<b>3 l/24h</b>
10°C - 80%	<b>6 l/24h</b>
15°C - 60%	<b>5 l/24h</b>
15°C - 80%	<b>8 l/24h</b>
20°C - 60%	<b>7 l/24h</b>
20°C - 80%	<b>10 l/24h</b>
25°C - 60%	<b>8 l/24h</b>
25°C - 80%	<b>13 l/24h</b>
27°C - 65%	<b>9 l/24h</b>
27°C - 80%	<b>15 l/24h</b>
30°C - 80%	<b>20 l/24h</b>
32°C - 80%	<b>22 l/24h</b>

Data Sheet DD20 LCD V1011